

P 522



Download photos and docs on qlima.com!



PORTABLE AIR CONDITIONER

Product data sheet

Brand name	Qlima	
Model	P 522	
Sound power level ¹	dB	65
Refrigerant GWP ²	Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 3 . This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 3 times thigher than 1 kg of CO ₂ , over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.	3
EER ² / EE-Class	W/W	2,61 / A
Indicative hourly electricity consumption (Qsd/h)	kW	0,8
Capacity (P rated) ²	kW	2,125

Product specifications

Colour	white	
EAN code	8713508777320	

Technical specifications

Power consumption	kW	0,814
Power consumption standby mode	W	0,5
Power supply	V/Hz/Ph	220-240 / 50 / 1
Current	A	3,54
Air flow ¹	m ³ /h	300
For rooms up to ¹	m ³	55-75
Dehumidification capacity ³	L/24 h	14,4
Operating range	°C	18-35
Thermostatic range	°C	18-32
Sound pressure level	dB(A)	54-56
Fan speed	3 positions	
Control	electronic / remote	
Refrigerant	type/charge (g)	R290 / 215
Refrigerant / GWP	3	
CO ₂ equivalent	tonnes	0,0006
Dimensions (w x d x h)	mm	420 x 310 x 700
Compressor type	rotary	
Protection class	IP	X0
Weight	kg	27
Guarantee	years	2

¹ To be used as indication

² Measured conform EN 14511-2011



³ Moisture removal at 35°C, 60% RH

Accessories

1 Hose adapter
1 Exhaust hose
2 Hose connectors
Remote control (with battery)
Manual

Most important spare parts

Spare part description	EAN Code



20 ft = 152
40 ft = 308
HQ = 456

W x D x H =
485 x 360 x 887 mm

Gross =
31 kg

Qlima
HOME MADE CLIMATES

P 522 PORTABLE AIR CONDITIONER



Remote control



3 Fan speed settings



Cooldown effect



Environmental friendly
refrigerant



Dehumidification function

Features

Electronic controls: The unit is equipped with electronic touch controls.

Fan speed setting: Select the fan speed: low, medium or high. The display will show the chosen speed.

Timer: Operating time to be set up to 24 hours. The unit switches off or on automatically when the set time has run down.

Air conditioning: The unit produces, with relatively high energy efficiency (A-rating), a pleasant and refreshing high capacity cool airflow. Unhealthy particles are captured by the air filters. Performance is optimal when the entering of warm outside air

Airflow: Move the air vent direction by adjusting the grill at the front side of the air conditioner and by moving the vertical and horizontal louvers.

Cooldown effect: The unit removes humidity by condensation. The condensate cools the condenser and is removed by the hot air discharge. This will increase the energy efficiency; the so called "cool down" effect.

Dehumidification: The unit can also be used as dehumidifier only. In that case the exhaust hose is not connected and warm air returns in the room.

Continuous drainage: In case of use as dehumidifier only it is necessary to connect a continuous drainage tube (not included) to the unit.

Exhaust duct: Hot air and humidity is transported, by an easy to install exhaust duct, outside the room.

Full colour box: The unit is delivered complete with auxiliary parts in a stylish full colour box showing application and operation information in multiple languages.

* Measured conform EN 14511