

# P 528

Download photos and docs on [qlima.com!](http://qlima.com!)



# PORTABLE AIR CONDITIONER



## Product data sheet

Brand name		Qlima
Model		P 528
Sound power level <sup>1</sup>	dB	65
Refrigerant GWP <sup>2</sup>	Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 3. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 3 times higher than 1 kg of CO <sub>2</sub> , over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.	3
EER <sup>2</sup> / EE-Class	W/W	2,6 / A
Indicative hourly electricity consumption (Qsd/h)	kW	1,0
Capacity (P rated) <sup>2</sup>	kW	2,640

## Product specifications

Colour		white
EAN code		8713508777337


## Technical specifications

Power consumption	kW	1,000
Power consumption standby mode	W	0,5
Power supply	V/Hz/Ph	220-240 / 50 / 1
Current	A	4,35
Air flow <sup>1</sup>	m <sup>3</sup> /h	290
For rooms up to <sup>1</sup>	m <sup>3</sup>	65-90
Dehumidification capacity <sup>3</sup>	L/24 h	26,4
Operating range	°C	18-35
Thermostatic range	°C	18-32
Sound pressure level	dB(A)	54-56
Fan speed		3 positions
Control		electronic / remote
Refrigerant	type/charge (g)	R290 / 205
Refrigerant / GWP		3
CO <sub>2</sub> equivalent	tonnes	0,0006
Dimensions (w x d x h)	mm	420 x 310 x 700
Compressor type		rotary
Protection class	IP	X0
Weight	kg	29
Guarantee	years	2

<sup>1</sup> To be used as indication

<sup>2</sup> Measured conform EN 14511-2011

<sup>3</sup> Moisture removal at 35°C, 60% RH



20 ft = 152  
40 ft = 308  
HQ = 456

W x D x H =  
485 x 360 x 887 mm

Gross =  
34 kg

## Accessories

1 Hose adapter

1 Exhaust hose

2 Hose connectors

Remote control (with battery)

Manual

## Most important spare parts

Spare part description	EAN Code

**Qlima**  
HOME MADE CLIMATES

# P 528 PORTABLE AIR CONDITIONER



Wireless smart control

## Features

---

**Wireless smart control:** The air conditioning is delivered with a convenient wireless smart control that enables a total control over your home comfort. Download the app and you can control your air conditioner with your smartphone from anywhere.

---



Remote control

**Electronic controls:** The unit is equipped with electronic touch controls.

---

**Fan speed setting:** Select the fan speed: low, medium or high. The display will show the chosen speed.

---



3 Fan speed settings

**Timer:** Operating time to be set up to 24 hours. The unit switches off or on automatically when the set time has run down.

---

**Air conditioning:** The unit produces, with relatively high energy efficiency (A-rating), a pleasant and refreshing high capacity cool airflow. Unhealthy particles are captured by the air filters. Performance is optimal when the entering of warm outside air

---



Cooldown effect

**Airflow:** Move the air vent direction by adjusting the grill at the front side of the air conditioner and by moving the vertical and horizontal louvers.

---

**Cooldown effect:** The unit removes humidity by condensation. The condensate cools the condenser and is removed by the hot air discharge. This will increase the energy efficiency; the so called "cool down" effect.

---



Environmental friendly refrigerant

**Dehumidification:** The unit can also be used as dehumidifier only. In that case the exhaust hose is not connected and warm air returns in the room.

---

**Continuous drainage:** In case of use as dehumidifier only it is necessary to connect a continuous drainage tube (not included) to the unit.

---



Dehumidification function

**Exhaust duct:** Hot air and humidity is transported, by an easy to install exhaust duct, outside the room.

---

**Full colour box:** The unit is delivered complete with auxiliary parts in a stylish full colour box showing application and operation information in multiple languages.

---

\* Measured conform EN 14511